

The advertisement features a large, angled LED display panel as the central focus. The panel is shown from a perspective that makes it appear to be floating or attached to a wall. The display itself is divided into two main sections: the top section shows a close-up of a red flower with water droplets, and the bottom section shows a blue and white pattern. To the left of the main panel, there is a vertical strip of the same LED technology, showing a grid of blue and white lights. The background is a mix of dark red, white, and light gray geometric shapes. The text 'LED P10 Outdoor' is prominently displayed in white on the red background. Below it, a short paragraph describes the product's features. At the bottom, the product is identified as a 'Heavy-Duty Outdoor LED Display'.

LED P10 Outdoor

Ultra-durable high-brightness display powered by high-performance P10 outdoor SMD technology. Seamless modular architecture featuring high refresh rates, weatherproof protection, and vibrant color accuracy.

Heavy-Duty Outdoor LED Display

Display & Optical

LED Arrangement:	SMD2727
Pixel Pitch:	10
Cabinet Resolution (W×H):	96*96
LED Module Resolution (W×H):	48*32
Brightness Level (nits):	7500
Visual View Angle (H/V):	160°/110°
Gray Scale:	16bit
Frame Rate (Hz):	≥3840

Physical & Mechanical

Cabinet Size (mm):	960*960*
Cabinet Acreage (m2):	0.5
Pixel Density (Dots/m2):	10000
LED Module Size (mm):	480*320
Cabinet Material:	Die-casting Aluminum

Power & Electrical Specs

Power Supply:	Taiwan
Maximum Power (W/m2):	≤700
Average Power (W/m2):	≤200
Voltage:	AC100~240V (50~60Hz)

Deep Hole Scanning Mode

LED Chip:	Nationstar
Operating Temperature/Humidity:	-20°C~+50°C; 10%~90%RH
Storage Temperature/Humidity:	-40°C~+60°C; 10%~90%RH
Service Life:	≥100,000Hrs
Maintenance Method:	Front/Back
Protecting Rating:	IP66
Certifications:	CE, FCC, ETL



